

TECHNICAL PRODUCT SHEET

Article ALEXANDER		Collection	Fabric group	CUSTOMS CODE 58011000
-----------------------------	--	------------	--------------	--------------------------

FABRIC TYPE

- | | | |
|--|---|--|
| <input type="checkbox"/> Fabric for decoration | <input checked="" type="checkbox"/> Fabric for upholstery | <input type="checkbox"/> Fabric for curtains |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

TYPE OF MANUFACTURING PROCESS

- | | | |
|--|---|---|
| <input type="checkbox"/> Fibre dyed | <input checked="" type="checkbox"/> Yarn dyed | <input type="checkbox"/> Piece dyed |
| <input type="checkbox"/> Cylinder printing | <input type="checkbox"/> Screen printing | <input type="checkbox"/> Digital printing |
| <input type="checkbox"/> Appliction | <input type="checkbox"/> Corosion | <input type="checkbox"/> Coating |
| <input type="checkbox"/> Embossing | <input type="checkbox"/> Embroidery | <input type="checkbox"/> Laser |
| DYES | | |
| <input type="checkbox"/> Direct | <input type="checkbox"/> Reactive | <input type="checkbox"/> Acid |
| <input type="checkbox"/> Pre-metallised | <input type="checkbox"/> Dispersed | <input type="checkbox"/> Others |

RECOMMENDED CLEANING INSTRUCTIONS



DESCRIPTIVE FEATURES

Origin of fabric	<input checked="" type="checkbox"/> EU	<input type="checkbox"/> non-EU
Product composition	54%WV 34%CO 12%PES (PILE 100% WV) Weave _____	
Warp repeat cm	<input type="text"/>	Weft repeat cm <input type="text"/>
Weight linear mt.	503	Weight sq. metre 345
Average roll length mt.	<input type="text"/>	Minimum roll length mt. <input type="text"/>
Fabric width with selvedge cm.	<input type="text"/>	Fabric width without selvedge cm <input type="text"/>
		Useable width cm 140

DIMENSIONAL STABILITY

	Warp	Weft	
Steam iron	110° C	1%	<i>Din 53894</i>
Washing with water	<input type="text"/>	<input type="text"/>	<i>ISO 5077/ISO6330</i>
Drycleaning	P	2%	<i>ISO 3175</i>

COLOUR FASTNESS

	Light colours	Dark colours	Pastel colours	
Xenotest light	4/5	4/5	4/5	<i>ISO 105-B02</i>
Washing with water	<input type="text"/>	<input type="text"/>	<input type="text"/>	<i>ISO 105-E01</i>
Drycleaning	4/5	4	4	<i>ISO 105-D01</i>
Dry abrasion resistance	4/5	4	3/4	<i>ISO105-X12</i>
Wet abrasion resistance	4	3/4	3	<i>ISO 105-X12</i>

MECHANICAL CHARACTERISTICS

Resistance to Martindale test 12k/Pa	N° rubs	30000		INTENSE USE	<i>ISO 12947-2</i>
Pilling resistance	500 rubs	4	2000 rubs	4	5000 rubs 4 <i>ISO 12945</i>