

TECHNICAL PRODUCT SHEET

Article FIFTYFIFTY		Collection	Fabric group	CUSTOMS CODE 55169300
------------------------------	--	------------	--------------	--------------------------

FABRIC TYPE

Fabric for decoration
 Fabric for upholstery
 Fabric for curtains

TYPE OF MANUFACTURING PROCESS

<input type="checkbox"/> Fibre dyed	<input checked="" type="checkbox"/> Yarn dyed	<input type="checkbox"/> Piece dyed
<input type="checkbox"/> Cylinder printing	<input type="checkbox"/> Screen printing	<input type="checkbox"/> Digital printing
<input type="checkbox"/> Application	<input type="checkbox"/> Corosion	<input type="checkbox"/> Coating
<input type="checkbox"/> Embossing	<input type="checkbox"/> Embroidery	<input type="checkbox"/> Laser

DYES

<input type="checkbox"/> Direct	<input checked="" type="checkbox"/> Reactive	<input type="checkbox"/> Acid
<input type="checkbox"/> Pre-metallised	<input type="checkbox"/> Dispersed	<input type="checkbox"/> Others



RECOMMENDED CLEANING INSTRUCTIONS






 WR

DESCRIPTIVE FEATURES

Origin of fabric EU non-EU
 Product composition **76% CV - 24% LI** Weave **JACQUARD**
 Warp repeat cm  Weft repeat cm 
 Weight linear mt. **831** Weight sq. metre **585**
 Average roll length mt. Minimum roll length mt.
 Fabric width with selvedge cm. **142** Fabric width without selvedge cm Useable width cm **138**


DIMENSIONAL STABILITY

	Warp	Weft	
Steam iron 110° C	2%	2%	Din 53894
Washing with water			ISO 5077/ISO6330
Drycleaning P	2%	2%	ISO 3175

COLOUR FASTNESS

	Light colours	Dark colours	Pastel colours	
Xenotest light	5/6	5/6	4/5	ISO 105-B02
Washing with water				ISO 105-E01
Drycleaning	4/5	4/5	4/5	ISO 105-D01
Dry abrasion resistance	5	4/5	4	ISO105-X12
Wet abrasion resistance	5	4	3/4	ISO 105-X12

MECHANICAL CHARACTERISTICS

Resistance to Martindale test 12k/Pa N° rubs **30000**  **INTENSE USE** ISO 12947-2
 Pilling resistance 500 rubs **3/4** 2000 rubs **3/4** 5000 rubs **3** ISO 12945