

TECHNICAL PRODUCT SHEET

Article <b>PLUSHY</b>		Collection	Fabric group	CUSTOMS CODE 55121990
--------------------------	--	------------	--------------	--------------------------


FABRIC TYPE

- Fabric for decoration      Fabric for upholstery      Fabric for curtains

TYPE OF MANUFACTURING PROCESS

- |  |  |  |
|--|--|--|
| <input type="checkbox"/> Fibre dyed        | <input type="checkbox"/> Yarn dyed       | <input checked="" type="checkbox"/> Piece dyed |
| <input type="checkbox"/> Cylinder printing | <input type="checkbox"/> Screen printing | <input type="checkbox"/> Digital printing      |
| <input type="checkbox"/> Application       | <input type="checkbox"/> Corosion        | <input type="checkbox"/> Coating               |
| <input type="checkbox"/> Embossing         | <input type="checkbox"/> Embroidery      | <input type="checkbox"/> Laser                 |
- DYES**
- |   |                                    |                                 |
|---|------------------------------------|---------------------------------|
| <input type="checkbox"/> Direct         | <input type="checkbox"/> Reactive  | <input type="checkbox"/> Acid   |
| <input type="checkbox"/> Pre-metallised | <input type="checkbox"/> Dispersed | <input type="checkbox"/> Others |

RECOMMENDED CLEANING INSTRUCTIONS



DESCRIPTIVE FEATURES

Origin of fabric	<input checked="" type="checkbox"/> EU	<input type="checkbox"/> non-EU
Product composition	<b>100% PES FR</b>	Weave _____
Warp repeat cm	↕ _____	Weft repeat cm ← _____
Weight linear mt.	<b>580</b>	Weight sq. metre <b>405</b>
Average roll length mt.	_____	Minimum roll length mt. _____
Fabric width with selvedge cm.	_____	Fabric width without selvedge cm _____ Useable width cm <b>142</b>

DIMENSIONAL STABILITY

	Warp	Weft	
Steam iron	<u>110° C</u>	<u>1%</u>	<u>1%</u> <i>Din 53894</i>
Washing with water	<u>30° C</u>	<u>2%</u>	<u>2%</u> <i>ISO 5077/ISO6330</i>
Drycleaning	<u>P</u>	<u>2%</u>	<u>2%</u> <i>ISO 3175</i>

COLOUR FASTNESS

	Light colours	Dark colours	Pastel colours	
Xenotest light	<u>5</u>	<u>5</u>	<u>4/5</u>	<i>ISO 105-B02</i>
Washing with water	<u>4/5</u>	<u>4/5</u>	<u>4/5</u>	<i>ISO 105-E01</i>
Drycleaning	<u>4/5</u>	<u>4/5</u>	<u>4/5</u>	<i>ISO 105-D01</i>
Dry abrasion resistance	<u>5</u>	<u>4/5</u>	<u>4/5</u>	<i>ISO105-X12</i>
Wet abrasion resistance	<u>4/5</u>	<u>4</u>	<u>3/4</u>	<i>ISO 105-X12</i>

MECHANICAL CHARACTERISTICS

Resistance to Martindale test 12k/Pa	N° rubs	<b>100000</b>		<b>INTENSE USE</b>	<i>ISO 12947-2</i>
Pilling resistance	500 rubs	<u>4</u>	2000 rubs	<u>4</u>	5000 rubs <u>3/4</u> <i>ISO 12945</i>