

TECHNICAL PRODUCT SHEET

Article SPLENDIDO		Collection	Fabric group	CUSTOMS CODE 58013700
-----------------------------	--	------------	--------------	--------------------------

FABRIC TYPE

<input checked="" type="checkbox"/> Fabric for decoration	<input checked="" type="checkbox"/> Fabric for upholstery	<input type="checkbox"/> Fabric for curtains
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

TYPE OF MANUFACTURING PROCESS

<input type="checkbox"/> Fibre dyed	<input type="checkbox"/> Yarn dyed	<input checked="" type="checkbox"/> Piece dyed
<input type="checkbox"/> Cylinder printing	<input type="checkbox"/> Screen printing	<input type="checkbox"/> Digital printing
<input type="checkbox"/> Application	<input type="checkbox"/> Corosion	<input type="checkbox"/> Coating
<input type="checkbox"/> Embossing	<input type="checkbox"/> Embroidery	<input type="checkbox"/> Laser
DYES		
<input type="checkbox"/> Direct	<input type="checkbox"/> Reactive	<input type="checkbox"/> Acid
<input type="checkbox"/> Pre-metallised	<input type="checkbox"/> Dispersed	<input type="checkbox"/> Others

RECOMMENDED CLEANING INSTRUCTIONS



IRON WITHOUT USING STEAM

DESCRIPTIVE FEATURES

Origin of fabric	<input checked="" type="checkbox"/> EU	<input type="checkbox"/> non-EU
Product composition	63%CV 26%CO 11%SE (PILE 85%CV 15%SE)	
Warp repeat cm	<input type="text"/>	Weft repeat cm <input type="text"/>
Weight linear mt.	1022	Weight sq. metre 730
Average roll length mt.	<input type="text"/>	Minimum roll length mt. <input type="text"/>
Fabric width with selvedge cm.	<input type="text"/>	Fabric width without selvedge cm <input type="text"/>
		Useable width cm 140

DIMENSIONAL STABILITY

	Warp	Weft	
Iron	<u>110°C</u>	<u>1%</u>	<u>1%</u> <i>Din 53894</i>
Washing with water	<u> </u>	<u> </u>	<u> </u> <i>ISO 5077/ISO6330</i>
Drycleaning	<u>P</u>	<u>2%</u>	<u>2%</u> <i>ISO 3175</i>

COLOUR FASTNESS

	Light colours	Dark colours	Pastel colours	
Xenotest light	<u>4</u>	<u>4/5</u>	<u>4/5</u>	<i>ISO 105-B02</i>
Washing with water	<u> </u>	<u> </u>	<u> </u>	<i>ISO 105-E01</i>
Drycleaning	<u>4/5</u>	<u>4</u>	<u>4</u>	<i>ISO 105-D01</i>
Dry abrasion resistance	<u>5</u>	<u>4</u>	<u>4</u>	<i>ISO105-X12</i>
Wet abrasion resistance	<u>4/5</u>	<u>3/4</u>	<u>3</u>	<i>ISO 105-X12</i>

MECHANICAL CHARACTERISTICS

Resistance to Martindale test 12k/Pa	N° rubs 50.000		INTENSE USE	<i>ISO 12947-2</i>
Pilling resistance	500 rubs <u>4/5</u>	2000 rubs <u>4</u>	5000 rubs <u>4</u>	<i>ISO 12945</i>