

**TECHNICAL PRODUCT SHEET**

Article <b>PRESENT PERFECT</b>	Collection	Fabric group	CUSTOMS CODE 53109000
-----------------------------------	------------	--------------	--------------------------

**FABRIC TYPE**

<input checked="" type="checkbox"/> Fabric for decoration	<input type="checkbox"/> Fabric for upholstery	<input checked="" type="checkbox"/> Fabric for curtains
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**TYPE OF MANUFACTURING PROCESS**

<input type="checkbox"/> Fibre dyed	<input checked="" type="checkbox"/> Yarn dyed	<input type="checkbox"/> Piece dyed
<input type="checkbox"/> Cylinder printing	<input type="checkbox"/> Screen printing	<input type="checkbox"/> Digital printing
<input type="checkbox"/> Application	<input type="checkbox"/> Corosion	<input type="checkbox"/> Coating
<input type="checkbox"/> Embossing	<input type="checkbox"/> Embroidery	<input type="checkbox"/> Laser
<b>DYES</b>		
<input type="checkbox"/> Direct	<input type="checkbox"/> Reactive	<input type="checkbox"/> Acid
<input type="checkbox"/> Pre-metallised	<input type="checkbox"/> Dispersed	<input type="checkbox"/> Others

**RECOMMENDED CLEANING INSTRUCTIONS**



**DESCRIPTIVE FEATURES**

Origin of fabric	<input checked="" type="checkbox"/> EU	<input type="checkbox"/> non-EU
Product composition	<b>47%JU 37%CO 6%PES 6%LI 2%PA 2%CV</b>	
Warp repeat cm	<b>105</b>	Weft repeat cm <b>69</b>
Weight linear mt.	<b>576</b>	Weight sq. metre <b>412</b>
Average roll length mt.		Minimum roll length mt.
Fabric width with selvedge cm.	Fabric width without selvedge cm	Useable width cm <b>138</b>
Weave <b>JACQUARD</b>		

**DIMENSIONAL STABILITY**

	Warp	Weft	
Steam iron	<b>110° C</b>	<b>1%</b>	<i>Din 53894</i>
Washing with water			<i>ISO 5077/ISO6330</i>
Drycleaning	<b>P</b>	<b>3%</b>	<i>ISO 3175</i>

**COLOUR FASTNESS**

	Light colours	Dark colours	Pastel colours
Xenotest light	<b>3/4</b>	<b>3/4</b>	<i>ISO 105-B02</i>
Washing with water			<i>ISO 105-E01</i>
Drycleaning	<b>4/5</b>	<b>4</b>	<i>ISO 105-D01</i>
Dry abrasion resistance			<i>ISO105-X12</i>
Wet abrasion resistance			<i>ISO 105-X12</i>

**MECHANICAL CHARACTERISTICS**

Resistance to Martindale test 12k/Pa	N° rubs	<i>ISO 12947-2</i>
Pilling resistance	500 rubs _____ 2000 rubs _____ 5000 rubs _____	<i>ISO 12945</i>