

**TECHNICAL PRODUCT SHEET**

Article <b>T19028 LUPO</b>		Collection	Fabric group	CUSTOMS CODE 55121990
-------------------------------	--	------------	--------------	--------------------------

**FABRIC TYPE**

<input type="checkbox"/> Fabric for decoration	<input type="checkbox"/> Fabric for upholstery	<input type="checkbox"/> Fabric for curtains
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**TYPE OF MANUFACTURING PROCESS**

<input type="checkbox"/> Fibre dyed	<input type="checkbox"/> Yarn dyed	<input type="checkbox"/> Piece dyed
<input type="checkbox"/> Cylinder printing	<input type="checkbox"/> Screen printing	<input type="checkbox"/> Digital printing
<input type="checkbox"/> Application	<input type="checkbox"/> Corosion	<input type="checkbox"/> Coating
<input type="checkbox"/> Embossing	<input type="checkbox"/> Embroidery	<input type="checkbox"/> Laser
<b>DYES</b>		
<input type="checkbox"/> Direct	<input type="checkbox"/> Reactive	<input type="checkbox"/> Acid
<input type="checkbox"/> Pre-metallised	<input type="checkbox"/> Dispersed	<input type="checkbox"/> Others

**RECOMMENDED CLEANING INSTRUCTIONS**



**DESCRIPTIVE FEATURES**

Origin of fabric	<input type="checkbox"/> EU	<input type="checkbox"/> non-EU		
Product composition	<b>74%PES FR TREVIRA 26%PES FR</b>		Weave	<b>JACQUARD</b>
Warp repeat cm	<input type="text"/>	Weft repeat cm	<input type="text"/>	
Weight linear mt.	<b>820</b>	Weight sq. metre	<b>575</b>	
Average roll length mt.	<input type="text"/>	Minimum roll length mt.	<input type="text"/>	
Fabric width with selvedge cm.	<input type="text"/>	Fabric width without selvedge cm	Useable width cm	<b>140</b>

**DIMENSIONAL STABILITY**

	Warp	Weft	
Steam iron	<u>110° C</u>	<u>1%</u>	<i>Din 53894</i>
Washing with water	<u>30°C</u>	<u>2%</u>	<i>ISO 5077/ISO6330</i>
Drycleaning	<u>P</u>	<u>2%</u>	<i>ISO 3175</i>

**COLOUR FASTNESS**

	Light colours	Dark colours	Pastel colours
Xenotest light	<u>5</u>	<u>4/5</u>	<u>ISO 105-B02</u>
Washing with water	<u>4/5</u>	<u>4/5</u>	<u>ISO 105-E01</u>
Drycleaning	<u>4/5</u>	<u>4/5</u>	<u>ISO 105-D01</u>
Dry abrasion resistance	<u>4/5</u>	<u>4/5</u>	<u>ISO105-X12</u>
Wet abrasion resistance	<u>4/5</u>	<u>4</u>	<u>ISO 105-X12</u>

**MECHANICAL CHARACTERISTICS**

Resistance to Martindale test 12k/Pa	N° rubs	<b>&gt; 40.000</b>		<b>INTENSE USE</b>	<i>ISO 12947-2</i>
Pilling resistance	500 rubs	<input type="text"/>	2000 rubs	<input type="text"/>	5000 rubs <u>4/5</u> <i>ISO 12945</i>