

TECHNICAL PRODUCT SHEET

Article <b>T19043 L'AGE D'OR</b>	Collection	Fabric group	CUSTOMS CODE 54079300
-------------------------------------	------------	--------------	--------------------------

FABRIC TYPE

- Fabric for decoration    
  Fabric for upholstery    
  Fabric for curtains

TYPE OF MANUFACTURING PROCESS

- |  |   |   |
|--|---|---|
| <input type="checkbox"/> Fibre dyed        | <input checked="" type="checkbox"/> Yarn dyed | <input type="checkbox"/> Piece dyed       |
| <input type="checkbox"/> Cylinder printing | <input type="checkbox"/> Screen printing      | <input type="checkbox"/> Digital printing |
| <input type="checkbox"/> Application       | <input type="checkbox"/> Corosion             | <input type="checkbox"/> Coating          |
| <input type="checkbox"/> Embossing         | <input type="checkbox"/> Embroidery           | <input type="checkbox"/> Laser            |
- DYES
- |   |                                    |                                 |
|---|------------------------------------|---------------------------------|
| <input type="checkbox"/> Direct         | <input type="checkbox"/> Reactive  | <input type="checkbox"/> Acid   |
| <input type="checkbox"/> Pre-metallised | <input type="checkbox"/> Dispersed | <input type="checkbox"/> Others |

RECOMMENDED CLEANING INSTRUCTIONS



DESCRIPTIVE FEATURES

Origin of fabric	<input checked="" type="checkbox"/> EU	<input type="checkbox"/> non-EU
Product composition	<b>36%WO 25%PES 21%CV 15%CO 3%PM</b>	
Warp repeat cm	<b>29</b>	Weft repeat cm <b>29</b>
Weight linear mt.	<b>473</b>	Weight sq. metre <b>320</b>
Average roll length mt.		Minimum roll length mt.
Fabric width with selvedge cm.		Fabric width without selvedge cm
		Useable width cm <b>145</b>

DIMENSIONAL STABILITY

	Warp	Weft	
Steam iron	<b>110° C</b>	<b>1%</b>	<i>Din 53894</i>
Washing with water			<i>ISO 5077/ISO6330</i>
Drycleaning	<b>P</b>	<b>2%</b>	<i>ISO 3175</i>

COLOUR FASTNESS

	Light colours	Dark colours	Pastel colours
Xenotest light	<b>4</b>	<b>4/5</b>	<i>ISO 105-B02</i>
Washing with water			<i>ISO 105-E01</i>
Drycleaning	<b>4/5</b>	<b>4/5</b>	<i>ISO 105-D01</i>
Dry abrasion resistance			<i>ISO105-X12</i>
Wet abrasion resistance			<i>ISO 105-X12</i>

MECHANICAL CHARACTERISTICS

Resistance to Martindale test 12k/Pa	N° rubs	<i>ISO 12947-2</i>
Pilling resistance	500 rubs _____ 2000 rubs _____ 5000 rubs _____	<i>ISO 12945</i>