

## TECHNICAL PRODUCT SHEET

Article <b>T21007 NIMBUS</b>		Collection	Fabric group	CUSTOMS CODE <b>51122000</b>
---------------------------------	--	------------	--------------	---------------------------------

### FABRIC TYPE

<input checked="" type="checkbox"/> Fabric for decoration	<input checked="" type="checkbox"/> Fabric for upholstery	<input type="checkbox"/> Fabric for curtains
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

### TYPE OF MANUFACTURING PROCESS

<input type="checkbox"/> Fibre dyed	<input checked="" type="checkbox"/> Yarn dyed	<input type="checkbox"/> Piece dyed
<input type="checkbox"/> Cylinder printing	<input type="checkbox"/> Screen printing	<input type="checkbox"/> Digital printing
<input type="checkbox"/> Application	<input type="checkbox"/> Corosion	<input type="checkbox"/> Coating
<input type="checkbox"/> Embossing	<input type="checkbox"/> Embroidery	<input type="checkbox"/> Laser

### DYES

<input type="checkbox"/> Direct	<input type="checkbox"/> Reactive	<input type="checkbox"/> Acid
<input type="checkbox"/> Pre-metallised	<input type="checkbox"/> Dispersed	<input type="checkbox"/> Others

### RECOMMENDED CLEANING INSTRUCTIONS



### DESCRIPTIVE FEATURES

Origin of fabric	<input checked="" type="checkbox"/> EU	<input type="checkbox"/> non-EU
Product composition	<u><b>70%WO 15%CO 10%PA 5%PES</b></u> Weave _____	
Warp repeat cm	<u>                    </u>	Weft repeat cm <u>                    </u>
Weight linear mt.	<u><b>1.040</b></u>	Weight sq. metre <u><b>735</b></u>
Average roll length mt.	<u>  </u>	
Fabric width with selvedge cm.	<u>                    </u> Fabric width without selvedge cm <u>                    </u> Useable width cm <u><b>140</b></u>	

### DIMENSIONAL STABILITY

	Warp	Weft	
Steam iron	<u><b>110° C</b></u>	<u><b>1%</b></u>	<u><b>1%</b></u> <i>Din 53894</i>
Washing with water	<u>                    </u>	<u>                    </u>	<u>                    </u> <i>ISO 5077/ISO6330</i>
Drycleaning	<u><b>P</b></u>	<u><b>2%</b></u>	<u><b>2%</b></u> <i>ISO 3175</i>

### COLOUR FASTNESS

	Light colours	Dark colours	Pastel colours
Xenotest light	<u><b>6/7</b></u>	<u><b>6</b></u>	<u>                    </u> <i>ISO 105-B02</i>
Washing with water	<u>                    </u>	<u>                    </u>	<u>                    </u> <i>ISO 105-E01</i>
Drycleaning	<u><b>4/5</b></u>	<u><b>4/5</b></u>	<u>                    </u> <i>ISO 105-D01</i>
Dry abrasion resistance	<u><b>4/5</b></u>	<u><b>4/5</b></u>	<u>                    </u> <i>ISO105-X12</i>
Wet abrasion resistance	<u><b>4</b></u>	<u><b>3/4</b></u>	<u>                    </u> <i>ISO 105-X12</i>

### MECHANICAL CHARACTERISTICS

Resistance to Martindale test 12k/Pa	N° rubs <u><b>&gt; 40.000</b></u>		<b>INTENSE USE</b> <i>ISO 12947-2</i>
Pilling resistance	500 rubs <u>                    </u>	2000 rubs <u>                    </u>	5000 rubs <u><b>4/5</b></u> <i>ISO 12945</i>